

Velocità Giri/min ¹	Speed R.p.m.	Geschw. U/min ¹	Velocidad R.p.m.	Vitesse Tours/min ¹
Carico statico max	Max static load	Max statische Achslast	Carga estatica max	Charge statique max

Differenza di tiro in kg con rendimento del vano = 0.8
 Out of balance load in kg with shaft efficiency = 0.8
 Zugkrafte in kg mit Schachtwirkungsgrad = 0.8
 Carga descompensada en kg con rendimento del hueco = 0.8
 Force de traction en kg avec rendement de la gaine = 0.8

VELOCITÀ SPEED GESCHW. VELOCIDAD VITESSE	RAPPORTO RATIO ÜBERSETZ. REDUCCIONES RAPPORT	PULEGGIA SHEAVE TREIBSCH. POLEA POULIE
--	--	--



2.2	2.6	3.2	3.5	4.0	4.4	5.1	5.6	5.9	6.5	[m / sec]		Ø mm
167	195	240	268	307	335	395				0.85	1/37	400
139	163	200	223	256	279	319				1.02	1/37	480
129	150	185	206	236	257	294				1.10	1/37	520
120	139	171	191	219	239	275				1.19	1/37	560
112	130	160	179	205	223	263				1.27	1/37	600
70	82	101	113	129	141	162	178	189	207	2.30	3/41	400
59	68	84	94	108	117	135	149	158	170	2.76	3/41	480
54	63	78	87	99	108	125	137	145	157	2.99	3/41	520
50	59	72	80	92	101	116	127	135	146	3.22	3/41	560
47	55	67	75	86	94	108	119	126	136	3.45	3/41	600