


PAWO F3

nominal diameter	6,0 mm
rope construction	6 x 19 Seale + IWRC
surface	ungalvanized
part-number	761406030



Special Rope for small Traction Sheaves with Type Examinaton Certificate

date of issue:
Oct. 2007

Technical data

- nominal diameter mm 6,0
- type of lay regular lay
- direction of lay right lay (sZ)
- tensile grade N/mm² 1960
- minimum breaking load kN 27,50
- calculated mass kg/m 0,145
- Ø-Tolerance (no load) % - 0 / + 3
- number of load bearing wires in the outer strands 114
- Technical specification: DIN EN 12385 part 2 + 4
- Material: GW-Liftquality and acc. to DIN EN 10264, ISO 4101

Hint :

The rope-Ø and the tensile grade don't comply with the requirements of the EN 81 part 1+2 and the DIN EN 12385 - 5

Details about the operational capability of the rope can be found on the corresponding type examination certificate No. G 454/1 of 2007-10-08.

GUSTAV WOLF

Seil- und Drahtwerke GmbH & Co. KG



P.O. Box 3353

Sundenstr. 40

D - 33332 Gütersloh

☎ +49 (0) 5241 / 876 - 0

📠 +49 (0) 5241 / 876 - 180

✉ info@gustav-wolf.de